

Features and Benefits

The Molex Fibre outlet available in 2 ports modular with adapter unloaded. This wall termination outlet is designed for FTTH applications, with standard 86*86mm dimensions to existing telephone/network connections it is well suited to home or office environments. The outlet can support up to 4 fibres, A variety of adaptors (LC/SC, & square ST, FC) can be used giving the user a flexible solution.

- Allows SC Simplex, LC duplex, and square flange ST/FC simplex adaptors to be installed
- Integral fibre management
- Accommodates splice protectors
- Multi point fibre entry
- Shutters for non-live ports
- Standard colour: white

Commerical Standards

Compliant to RoHS, Reach / SVHC
 Designed in accordance with
 TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1

Technical Information

Material: ABS UL94V-0
 Operating Temperature: -40°C to + 50°C
 Dimension: 86 x 86 x 27 mm
 Optional Optical Cables: Figure '8' soft cable, general outdoor cable, indoor wiring FTTH drop cable



ORDERING INFORMATION

Order No.	SAP No.	Description
AFR-00549	180600323	2 Port Fiber Wall Outlet, Unloaded, White

MOLEX PREMISE NETWORKS

Americas
 Tel: 630 969 4550
 www.molexpn.com

EMEA
 Tel: 44 (0)2392 205800
 www.molexpn.co.uk

APAC
 Tel: 61 3 9971 7111
 www.molexpn.com.au